



E.H. WACHS®
 Superior Equipment. Complete Support.™
 Vynikající zařízení. Komplexní podpora.

Elektrický pohon Electric Power Drive

EPD

SPECIFICATIONS

Funkce systému

Electric Power Drive for E.H. Wachs LCSF split frame models 206/3 and larger, EP 424 Form Tool and EP 424 Single Point models

EPM (pohonný elektromotor):

Powder coated AC high frequency inertia brushless motor with aluminum housing and gear box, high voltage, current spike and over temperature protected. Output speed infinitely variable.

EPB (řízený zdroj):

20 foot (6M) power cord and motor cables. Power cord ships without wall receptacle, user installation required

Konstrukce dálkového ovladače:

Black thermal plastic housing with stop/start, e-stop, motor speed control and hold to run trigger, 20 foot (6M) cable

EPM Power Requirements:

230V (single phase), 400V (3 Phase), & 480V (3 Phase)
 50Hz-60Hz 15-20 Amp Service



Highly Portable Power Controller Sets up in minutes.



Once mounted, the lightweight EPM (Electric Power Motor) is out of the way.



Standard drive insert works with LCSF Low Clearance Split Frame and EP 424 End Prep Machines



Power controller is compact and portable, includes lock out tag out closure and top mounted controls

EPM (Electric Power Motor) Specs

| VOLTAGE (Phase) | POWER | Speed (RPM) | EPM Part # | Freq. | Amps | Weight | |
|-----------------|-------|-------------|------------|-----------|--------|--------|----|
| | | | | | | Lbs | KG |
| 230V (Single) | 8 KW | 160/250 | EPM8AS | 50- 60 Hz | 15-20A | 15.5 | 7 |
| 400V (Triple) | | | | | | | |
| 480V (Triple) | | | | | | | |

EPB (Electric Power Box) Controller Specs

| VOLTAGE (Phase) | POWER | EPB Part # | Freq. | Amps | Weight | |
|-----------------|---------|------------|-----------|--------|--------|------|
| | | | | | Lbs | KG |
| 230V (Single) | 8-12 KW | EPB 480 AS | 50- 60 Hz | 15-20A | 36.5 | 16.5 |
| 400V (Triple) | 8-12 KW | | | | | |
| 480V (Triple) | 8-12 KW | | | | | |

All product specifications provided are subject to change. Please contact the factory for the latest information on available models and features.

CONTACT US FOR A DEMO OR QUOTE

E-mail: info@ehwachs.com

Telephone: +1.847.537.8800

Fax: +1.847.520.1147

Visit our website: ehwachs.com

Worldwide Headquarters

600 Knightsbridge Parkway
 Lincolnshire, Illinois 60069



All dimensions shown for pipe diameters are US nominal diameters in inches, plus metric nominal diameters (DN) in parenthesis. Tubing and solid diameters if shown are actual US inches plus metric millimeter equivalents.